

# MATERIAL SAFETY DATA SHEET

DETRO MANUFACTURING, INC.  
1721 S.E. GRACE AVE. UNIT E.  
BATTLE GROUND, WA. 98604  
Phone: (360) 687-9960  
Fax: (360) 687-7284

## Section I - Identity of Product

Trade Name: Strippable Booth Coating #7300 / #7305 / #7350  
HHIS CODES: H F R P  
                  0 0 0 A

## Section II - Hazardous Ingredients

INGREDIENTS	CAS #	EXPOSURE LIMITS			VAPOR PRESSURE		WEIGHT %
		OSHA PEL	ACGH/TLV	OTHER	Hg @	TEMP	
1,2 Propanediol	57-55-6	NE	NE	50 ppm	0.1	68 F	5.0%
2,2,4 Trimethyl-1,3-pentanediol monoisobutyrate	25265-77-4	NE	NE	NE	0.0	68 F	5.0%
Silicon Dioxide (Amorphous)	7631-86-9	80 mg/M3	10 mg/M3	3 mg/M3	N/A		5.0%
*Vinyl Acetate Monomer	108-05-4	10 ppm	10 ppm	20 ppmSTEL	N/A		0.11%

\* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

\*\*\* This MSDS complies with the OSHA Hazard Communication Standard \*\*\*

## Section III - Physical Data

Boiling Point: basically water  
Evaporation Rate: slower than ether  
Appearance and Odor: Mild smelling thickened liquid  
Weight per gallon: 9.78 lbs.  
Solids per Gallon by Weight 40.67%

Water Solubility: Miscible  
Specific Gravity (H2O=1) 1.2  
Coating VOC: 1.12 LB/GL (135 G/L)  
Material VOC: 0.40 LB/GL (48 G/L)  
0.096 lbs VOC/lbs Solids

## Section IV - Fire and Explosion Hazard Data

Flash Point: N/A  
Flammable limits in air by volume: LOWER: 0.6% UPPER: 12.5%  
Extinguishing Media: CO<sub>2</sub>, Dry Chemical, Alcohol foam, Water fog.  
**Special Fire Fighting Procedures.** Avoid confined spaces. Wear full protective equipment including a positive pressure NIOSH-approved self-contained breathing apparatus  
**Unusual Fire and Explosion Hazards:** Closed containers exposed to high temperatures may burst due to steam buildup. : Cool containers with water fog

## Section V - Health Hazard Data

Permissible Exposure Level : Refer to section II

### **Effects of Overexposure:**

Skin: Prolonged and repeated contact can cause irritation.  
Eyes: Can cause irritation, redness, tearing.  
Swallowing: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.  
Inhalation: Adverse health effects from vapors or spray mist in poorly ventilated areas may include irritation of the mucous membranes of the nose, throat, respiratory tract and symptoms of headache and nausea.

### **First Aid:**

Skin: Wash with soap and water after use.  
Eyes: Wash with water, if irritant evident, see physician.

# MATERIAL SAFETY DATA SHEET

Swallowing: Seek immediate medical attention.  
Inhalation: Remove individual to fresh air, if breathing is difficult administer oxygen. If breathing has stopped give artificial respiration, get immediate medical attention.

## Section VI - Reactivity Data

Stability: Stable  
Hazardous Polymerization: Will not occur.  
Hazardous Decomposition: Incomplete combustion may release carbon monoxide, carbon dioxide and oxides of nitrogen.  
Incompatibility: Avoid strong oxidizing agents.

## Section VII - Spill or Leak Procedure

Dike, contain or absorb with inert material and transfer to containers for recovery or disposal. Disposal should be done in accordance with prevailing regulations. Prevent runoff into streams, sewers or other bodies of water.

## Section VIII - Special Protection Information

Respiratory: Use NIOSH/MSHA approved organic vapor respirator if TVL is exceeded.  
Ventilation: Use adequate ventilation to maintain exposure below TLV.  
Protective Equipment: Chemical splash goggles, Polyethylene gloves.

## Section IX - Regulatory Information

Sara Title III Section 313: None  
Prop 65: None (Carcinogen and Tetratogen)

Because we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our products in any individual situation. For the same reason, the products discussed are sold without warranty, expressed or implied. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability of this product for their intended use.