

MATERIAL SAFETY DATA SHEET

Page 1 of 2

Detro Manufacturing
1721 SE Grace Ave Unit E
Battle Ground, WA 98604
Phone: (360) 687-9960
Fax: (360) 883-7284

Section I - Identity of Materials

Trade Name: Washable Booth Coating #7301

Health = 1
Fire = 1
Reactivity = 0

Section II - Hazardous Ingredients

Ingredients	CAS #	Weight %	Exposure Limits		VP mm Hg
			ACGIH/TL V	OSHA/PEL	
Methyl Alcohol* (<1.0%) *Skin absorbable	67-56-1	No data	200 PPM	200 PPM	17.53

All ingredients in this product are listed in the T.S.C.A. inventory.

Section III - Physical Data

Boiling Point: 212 deg F	Vapor Density: (air=1) 1.2
Evaporation Rate: No data	Specific Gravity: (H ₂ O=1) 1.02
Volatiles Volume: No data	Vapor Pressure (mm Hg): 17.53
Appearance and Odor: Clear liquid, alcohol	Solubility in Water: Complete

Section IV - Fire and Explosion Hazard Data

Flash Point:	> 200 deg. F
Extinguishing Media:	Water spray, alcohol foam, CO ₂ , dry chemical, water fog.
Special Fire Fighting Procedures:	Wear self contained breathing apparatus with a full facepiece operated in positive pressure demand mode when fighting fires.
Unusual Fire and Explosion Hazards:	Containers may explode when exposed to extreme heat. Cool unruptured containers with water.

Section V - Health Hazard Data

Permissible Exposure Level : Refer to section II

Effects of Overexposure:

Skin:	May cause slight irritation (after prolonged and repeated contact). Symptoms may include redness, swelling and itching.
Eyes:	May cause slight irritation. Symptoms may include redness, swelling, pain and tearing.
Swallowing:	Can cause gastrointestinal irritation. Symptoms may include abdominal pain.
Inhalation:	May irritate respiratory tract. Symptoms may include soreness of nose and throat, coughing and sneezing.

MATERIAL SAFETY DATA SHEET

Page 2 of 2

First Aid:

Skin: Wash with soap and water. If irritation persists seek medical attention.
Eyes: Flush immediately with cold water for 15 minutes, and seek immediate medical attention.
Swallowing: Do not induce vomiting. Drink two glasses of water and seek immediate medical attention.
Inhalation: Remove individual to fresh air, if breathing is difficult administer oxygen. If breathing has stopped give artificial respiration, get immediate medical attention.

Section VI - Reactivity Data

This product is stable and hazardous polymerization will not occur. Incomplete combustion may release carbon monoxide and/or carbon dioxide. Incompatible with strong oxidizing agents, strong acids and strong bases.

Section VII - Spill or Leak Procedure

Clean up with approved material. Disposal should be done in accordance with prevailing regulations.

Section VIII - Special Protection Information

Respiratory Protection: Use NIOSH/MSHA approved respirator.
Ventilation: Mechanical ventilation may be necessary to maintain contaminants below TLV.
Protective Gloves: Wear impermeable gloves.
Eye Protection: Wear goggles.

Section IX - Special Precautions

Keep away from heat, sparks, open flame, and other sources of ignition. Immediately wipe, mop or pick up spill. Caution - floors covered with residual material are extremely slippery when wet.

Section X - Regulatory Information

Sara Title III Section 313: None
Prop 65: None (Carcinogen and Tetratogen)
VOC: 5 g/L (0.04 lb/ gl) EPA method 24
VOC Less Water and Exempt Solvents: 46 g/L EPA method 24
EPCRA Hazard Class: Fire hazard - yes, Pressure - no, Acute - yes, Chronic - yes.

Because we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information of the suitability of our products in any individual situation. For the same reason, the products discussed are sold without warranty, expressed or implied.